

General Disclaimer

One or more of the Following Statements may affect this Document

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.

Umbilical Design

Alan Littlefield / NE-D

August, 2007

Umbilical Design

- About Me - School:
 - BS Mechanical Engineering, Florida Tech, 1982
 - MS Mechanical Engineering, Florida Tech, 1987
- About Me – Work:
 - 22 years in Design Engineering
 - 2 years in Facilities Engineering
 - HVAC
 - Cranes
 - 18 years in Launch Accessories / Mechanical GSE Design
 - Umbilicals
 - Access Arms / Equipment
 - Handling Equipment
 - Test Facilities
 - Cryogenics
 - 2 years in Systems Engineering and Integration

Umbilical Design

- About Me – Programs / Projects:
 - KSC / CCAFS Facilities
 - Space Shuttle
 - Space Station GSE
 - X-33
 - Experimental / Test Facilities
 - Flight Hardware Design
- About Me – Umbilicals Experience
 - Shuttle SRB Joint Heater Umbilical
 - Shuttle Tail Service Mast
 - Shuttle ET GH2 Vent
 - Shuttle ET GO2 Vent
 - Shuttle Orbiter Mid-Body Umbilical
 - Rise-Off Umbilical Prototype
 - X-33 Umbilicals
 - Mars Umbilical Technology Demonstrator

T-0 Umbilical Types

- Rise-off (Bottom Mount)
 - Shuttle SRB Joint Heater
- Side Mount:
 - Tilting
 - Tail Service Masts (TSM)
 - Shuttle TSM
 - Long Masts
 - Redstone
 - Tilt-Up
 - Apollo TSM
 - Drop
 - Swing
 - Apollo Forward Umbilicals
 - “Pull Off”
 - Delta IV ECS

Umbilicals

- Umbilicals Typically Provide Commodities to a Launch Vehicle or Spacecraft.
- Different Types of Umbilicals
 - Ground to Ground
 - Ground to Flight (Focus of this Presentation)
 - Flight to Flight
- Typically T-0 Connections
 - Non T-0 are Typically Service Connections
- Commodities
 - Liquid Fuels / Oxidizers
 - High Pressure Gases
 - ECS
 - Power
 - Data
 - HazGas Sense


T-0 Umbilical Terminology

- Flight Carrier Plate:
 - Mechanical assembly grouping multiple individual connectors and attach and release mechanisms.
- Ground Carrier Plate:
 - Mechanical assembly grouping multiple individual connectors and attach and release mechanisms, also provides attachment to ground systems.
- Compliance Device or Mechanism:
 - Allows relative motion between vehicle and ground.
- Release Mechanism:
 - Disconnects flight and ground connectors or carrier plates.
- Retract Mechanism:
 - Withdraws ground connector or carrier plate to safe area following disconnect.
- Excursions:
 - Motions of vehicle prior to lift-off
- Drift:
 - Motions of vehicle following lift-off


T-0 Umbilical, X-33



T-0 Umbilical Plates



Flight Panel





Ground Panel

T-0 Umbilical Components

- Struts
 - Main / Compliance
 - Mating
 - Centering
- Collets / Receptacles
- Shear Pins
- Feet / Receptacles (Perches)
- Shock Absorbers / Energy Absorbers
- Drop Weights
- Pryotechnics
- Non Explosive Actuators
- Frangible Components
- Lanyards
- Blast Doors
- Latches

T-0 Umbilical Components



T-0 Umbilical Design Considerations

- Fault Tolerance / Failure Modes
- Vehicle Loads
- Connector Loads / Alignment
- Disconnect Dynamics
- Line Management
- Leakage
- Hazardproofing
- Excursions
- Trajectories / Drift
- Blast / Induced Environments
- Natural Environments
- Cryogenics / Shrinkage

T-0 Umbilical Design Considerations

- Fault Tolerance / Failure Modes
 - Fail Operational, Fail Operational, Fail Operational Where Practical
 - Particularly for Disconnect
 - Also for Attachment
 - Simplicity
 - Reliability
 - Like vs Unlike Redundancy

T-0 Umbilical Design Considerations

- Vehicle Loads
 - Typically Very Limited
 - Mating
 - Tanking
 - Disconnect
 - Primary
 - Secondary
 - Shear
 - Tension

T-0 Umbilical Design Considerations


- Connector Loads
 - Mating (Static)
 - Pressurization (Dynamic)
 - Can be Significant – Kips
 - Best if Balanced on Plate
- Connector Alignment
 - Axial
 - Lateral
 - Angular
 - Static
 - Rotational (Mating or Disconnect)
 - Fluid vs Electrical
- Deadfacing / Depressurization

T-0 Umbilical Design Considerations

- Disconnect Dynamics
 - Clearances
 - Dynamic Envelope
 - Drift
 - Timing
 - Primary
 - Secondary
 - Retraction
 - Deceleration
 - Protection / Covers


T-0 Umbilical Design Considerations

- Line Management
 - Loads
 - Bend Radii
 - Torsion
 - Tangling
 - Function
 - Drainage
 - Kinking
 - Protection




T-0 Umbilical Design Considerations

- Leakage
 - Ambient
 - Cryogenic
 - Alignment
 - Preload
 - Monitoring



T-0 Umbilical Design Considerations

- Hazardproofing
 - Purges
 - Purge Cavities / Isolation
 - Arrangement / Grouping
 - Sparking
 - Deadfacing
 - Drainback / Sweep Purges
 - HazGas Detection / Leakage



T-0 Umbilical Design Considerations

- Excursions
 - Mis-alignment or Relative Motion Between Umbilical and Vehicle
 - Excursions Vary by Operations Mode – Mating, Tanking, Abort, etc.
 - Static Excursion “Types”
 - Stacking Tolerances
 - Vehicle Manufacturing Tolerances
 - Dynamic Excursion “Types”
 - Thermal Movement
 - Wind Induced Oscillation
 - Payload Installation
 - Tanking / Cryo Shrinkage
 - Engine Buildup / Shutdown
 - Launcher / Tower Deflections

T-0 Umbilical Design Considerations

- Trajectories / Drift
 - Motion of the Vehicle after Lift-Off
 - Nominal Trajectory
 - Misc. Dispersions
 - Delays (“lift-off” not at T-0)
 - Wind / Drift
 - Other Environmental
 - Payload Variations
 - Off Nominal Trajectories
 - Vehicle Failures
 - Engine “Out” Conditions
 - Avoid Re-Contact

T-0 Umbilical Design Considerations



- Blast / Induced Environments
 - Blast Loads May Be Significant
 - Time to Protect Umbilical Varies
 - Pressure
 - Gas
 - Particle
 - » Erosion
 - Radiant Heating
 - Vibration
 - Pre-Launch
 - Post Launch
 - Ignition Over-Pressure
 - Acoustics / Vibro-Acoustics

T-0 Umbilical Design Considerations

- Natural Environments
 - Rain
 - Water Intrusion
 - Ice Formation
 - Wind
 - Wind Driven Rain
 - Temperature / Humidity / Corrosion

T-0 Umbilical Design Considerations

- Cryogenics / Shrinkage
 - Temperature Control / Insulation
 - Ice / Frost
 - Liquid Air
 - Purge
 - Thermal Control
 - Humidity Control
 - Shrouds
 - Thermal Distortion
 - Thermal Gradients
 - CTE Mismatch




T-0 Umbilical Testing

- Development Testing
 - Prototypes
 - “Proto-Flight”
 - Breadboard
- Qualification Testing Typically Performed in Launch Equipment Test Facility
 - GSE
 - Actual GSE Prior to Shipment
 - Similar GSE Prior to Shipment
 - Prototype GSE / LETF Dedicated GSE
 - Flight Plates
 - Dedicated LETF Plates
 - Actual Flight Plates
- Validation Testing Performed on Launcher or at Pad
 - Uses Actual GSE in Launch Configuration
 - Flight Hardware Options
 - None
 - TSE
 - Pathfinder / “Iron Bird”
 - Flight Vehicle



T-0 Umbilical Testing



T-0 Umbilical Testing



T-0 Umbilical Testing



T-0 Umbilical Testing

- Test Objectives to Simulate Processing / Pad Operations
 - Mating
 - Pad Stay
 - Tanking
 - Build-up
 - Abort / Shut-Down
 - Launch
 - Primary Disconnect
 - Failure Modes
- Tests Included:
 - Static Excursions
 - Dynamic Excursions
 - Lift-Off / Drift
 - Cryogenic Operation
 - Wind
 - Rain
- Tests Excluded:
 - Blast / Heat (Induced)
 - Vibration
 - Acoustics
 - Heat / Cold (Natural)